



2 MP 4G PTZ CAMERA

SS-IW220X-4G

Key Feature

- Support H.265/H.264 compression, Dual stream, video output
- Support Onvif, Support P2P function
- 2-way Audio Support
- Support up to 128G microSD card storage
- IP66 Compliant
- Support built-in PoE (optional)

Product Specifications:

Model No.

Camera

Sensor	1/2.8" 2MP CMOS Sensor
Effective Pixel	1920x1080
Min Illumination	Color: 0.01Lux @F1.2, 0Lux with IR on
Lens	4.7-94mm
Optical Zoom	20X
BLC	Support
AGC	Auto/manual
White Balance	Auto/manual/indoor/outdoor
S/N Ratio	>50dB
LED	8 Pcs IR & White Light LED
IR distance	Up to 80 meters

Lens

Focal Length	4.7-94mm
Optical Zoom	20X
Angle of View	61.4°~3.6°

Audio

Audio compression	G.726/G.711
Audio code rate	8Kbps, 16bit
Audio In/Out	Built-in MIC and speakers, support two-way audio

PTZ

Pan Range	0°~350°
Tilt Range	0°~90°
Pan Speed	6°-25°/S
Tilt Speed	3°-15°/S
Preset	256 Presets
Cruise	Support

Event

Motion Detection	4 Detection Area, 1-100 sensitivity
Human Detection	Support
Event Linkage	Alarm, SD Card Recording, Capture (Snap), Email, Push Notification, FTP Upload

4G

4G standard	FDD-LTE/TDD-LTE
4G frequency range	B1(2100MHz), B3(1800MHz), B7(2600MHz), B8(900MHz), B20(800MHz), B38(2600MHz), B40(2300MHz), B41(2500MHz)

Interface

Micro SD Card	Support up to 128G micro-SD card
Reset button	Support, press for 5 seconds to reset the camera
Sim Card	Micro SIM card, Plug and play, no need to set
Power	5.5*2.1mm power interface

General

Power Supply	DC 12V/2A±10%
Power consumption	Max 6W, Max 19W (with IR ON)
Operating Temperature	-20°C~+60°C (-4°F~+140°F),
Operating Humidity	10%~90%, non-condensing
Material	Metal shell
Ingress Protection	IP66
Product size	190mm×130mm×235mm(L×W×H)
Product weight	1.4kg