

## 3MP Bullet IP Camera

- High Resolution 3MP
- H.265 Compression
- **Intelligent Analytics Supported:** Human Detection, Intrusion Detection, Line crossing Detection.
- SD card supported up to 512GB.
- IP66 Compliant
- NDAA Compliant



### HD Resolution

Our Silver Series Camera comes with HD resolution, regardless of the moving pace, the camera does a good job of capturing detailed images.



### AI Video Analytics

Intelligent Analytics provides real time data with high accuracy which includes Human detection, Intrusion detection, Line crossing detection.

### Storage Capacity

Sparsh Silver series offer 512 GB high performing edge storage solution option for recording video and other functions.



## Technical Specifications:

Specifications	SC-IS30B-6P4	SC-IST30B-6P4
Camera		
Image sensor	1/2.8" Progressive CMOS Sensor	
Effective Pixels	2304(H)x1296(V)	
Min. Illumination	Color: 0.01 Lux @F1.2, B/W: 0.001 Lux@F1.2, 0 Lux at IR ON	
S/N Ratio	>60dB	
IR Distance	30-40Mtr	
Shutter Speed	1/50 sec ~ 1/10000 sec	
IR On/Off Control	Auto/ Manual	
IR LEDs	36IR Smart LEDs	
Lens		
Lens Type	Fixed	
Mount Type	M12	
Focal Length	6mm	
Max. Aperture	F2.0	
Angle Of View	6mm:57°(H)34°(V)64°(D)	
Focus Control	Fixed	
Video		
Compression	H.265+/H.265/H.264	
Streaming Capability	2 Streams	
Resolution	3MP/2MP/D1/ VGA/ CIF	
Streams	Mainstream: 3MP(2304x1296)/2MP (1920×1080) @25fps Sub Stream: 704x576 (D1), 640x480 (VGA), 352x288 (CIF) @25fps	
Bit Rate	221Kbps-8192Kbps	
Bit Raye Control	CBR/VBR	
Day/ Night	Automatic/Black and white	
Exposure Mode	Automatic/Manual-(1/50 sec ~ 1/10000 sec)	
BLC Mode	On/Off	
HLC Mode	On/Off	
Profiles	Auto, Low Light Priority, High Light Priority	
White Balance	Automatic	
Gain Control	Auto	
Noise Filter	Auto (1-5 Levels)	
Digital Zoom	16X, Area's selection with Mouse	
Anti - Flicker	On/Off	
AE Reference	1-255 Level	
AE Sensitivity	1-10 Level	



\*Product specifications & appearance are subject to change without prior notice or obligation.

Flip	Off / On	
IR Reverse	Support	
Mirror	Off / On	
Text Overlay	Title, Date & Time, Weekday	
Privacy Masking	Yes (4 zones)	
Events		
Motion Detection	22X18 Zones	
Video Blind	Support	
Abnormality	No Disk, Disk Error, Disk No Space, Network Cable Disconnected, IP Address Conflict	
Smart Functions	Human Detection, Intrusion Detection, Line crossing, Vehicle Detection, Video Blind	
Event Actions	Record alarm, Linkage alarm output, Sound alarm, Email link, Upload FTP, Snapshot	
PTZ (Manual)		
Pan	0° ~360°	
Tilt	0° ~90°	
Rotation	0° ~360°	
Safety		
Security	Authorized username and password, HTTPS with password, RTSP Validation, User Access Log, User Authentication, IP/MAC filtering; HTTPS; trusted upgrade	
ONVIF Authentication	ON, OFF	
RTSP Authentication	Digest, None	
Network		
Ethernet	10/100M adaptive Ethernet interface	
Protocol	TCP/IP, IPv4, ICMP, HTTP, HTTPS, HTTP-Base64, HTTP-Digest, DHCP, DNS, DDNS, RTP, RTSP, RTCP, NTP, UPnP, SMTP, FTP, IGMP, P2P,IP Filter	
Interoperability	ONVIF Profile S & G	
Max. user Access	30 Users	
Edge storage	Local PC for instant recording, one clicks Snapshot, one clicks triple Snapshot	
Web Viewer	IE, Chrome, Firefox, Safari	
Management Software	Sparsh VMS	
Smart Phone	Supports SVMS APP for iPhone, Android	
Interface		
SD Card	N/A	Support up to 512GB
General		
Operating Conditions	-30° C ~ +60° C (-22° F ~ +140° F) / Less than 95% RH	
Storage Conditions	-30° C ~ +60° C (-22° F ~ +140° F) / Less than 95% RH	
Ingress Protection	IP66	
Vandalism Protection	NA	
Power supply	DC 12V ± 10%, Optional: PoE (802.3af, class 3)	
Power Consumption	Max 12W	
Dimension & Weight	166mm(L) x67mm(H) x 66mm(W), 160g	



\*Product specifications & appearance are subject to change without prior notice or obligation.



Product Certification

Safety: CE, FCC, IS/EN:60950-1, IS:13252 (Part 1): 2010, BIS Registered

**Ordering Information:**

Sr. No.	Ordering Model	WDR	SD Card	IR Range
1.	SC-IS30B-6P4	80dB	NA	Up to 40M
2.	SC-IST30B-6P4	80dB	Yes	Up to 40M



\*Product specifications & appearance are subject to change without prior notice or obligation.