



2MP VEHICLE MOUNT PTZ

SS-IPRDOP-(X)

Key Feature:

- Resolution: 2 MP
- Video Compression: H.265/H.264
- IR Range: up to 100mtr
- Vibration & Shock proof Design
- Ultra-Wide Voltage Support
- Suitable for Vehicle Top Mount Installations
- IP67 Weatherproof Design

Product Specifications:

Model No.	20X
Camera	
Image Sensor	1/2.8" Progressive Scan CMOS
Effective Pixel	(1920x1080)
Min. Illumination	Color: 0.05Lux @F1.6, B/W: 0.005Lux with IR on
WDR	80dB
Shutter Time	1/100000s~1s
Day & Night	ICR Filter Auto Switch
S/N	>55dB
LEDs	4 High Power LED Lamps
Lens	
Focal Length	4.7-94mm @F1.6~F3.5
Optical Zoom	20X Optical Zoom
Zoom Speed	Approx 1s (Optical Wide-Tele)
Field of View	Wide:58.9°×45.3°Tele:2.11°×1.61°
Minimum Working Distance	100~1500mm (Wide-Tele)
PTZ	
Pan Range/Pan Speed	360° endless/ Pan Speed: 0.1°~100°/s
Tilt Range/Tilt Speed	-30°~90°/ Tilt Speed: 0.1°~60°/s
Preset Quantity	255
Patrol	4 Patrols
Scan	Support
Park Function	Support
IR	
IR Distance	Up to 150m
IR Angle	Auto/Manual
Video	
Max. Image Resolution	1920x1080
Primary Stream	25/30fps@ (1920x1080, 1280x960, 1280x720)
Secondary Stream	25/30fps@ (D1, VGA, CIF)
Video Compression	H.265/H.264
Video Bit Rate	32Kbps~16Mbps (CBR/VBR Adjustable)
Image Setting	Brightness/Contrast/Saturation/Sharpness
Audio	
Audio Compression	G.711
Audio I/O	1 IN(Optional)
Sampling Rate	16K,32K,64K,128K

Alarm

Alarm I/O 1 IN/1 Out (Optional)

General

Ethernet 1*RJ45 10M/100M Ethernet Port

Working Condition Temperature: -30°C~60°C / Humidity: 0~95%(Non-condensing)

Power Supply DC 9~36V

Power Consumption 15W MAX

Surge Protection IP67 Compliant, IK10 Certified, Level 2 lightning protection 6000V surge protection

Dimensions/Weight Φ125mmX118X222mm/2.35Kg

 Warranty Safety: CE, FCC, IS 13252-1 (2010), EN:60950-1, IEC 60950-1:2005, BIS Registered
 Immunity: CE, FCC

*Note: Product design specifications and colors are subject to change without notice to improve Reliability, Function or Design or otherwise. Errors and omissions excepted.

Images displayed here are for illustration purposes only, actual product may vary.

Sparsh offers customized products and solutions as per site or customer requirements, minor changes in specifications and appearance are warranted and tracked version wise for customized requirements.