

4MP Bullet IP Camera

- 4MP 1/2.8" CMOS image sensor, low luminance, and high-definition image
- Quad Streaming
- Intelligent Analytics Supported: People Counting, Vehicle Counting, Human Detection, Electronic Fence (Entry, Exits & Loitering Detection), Line Crossing, Wrong Direction Detection (Retrograde Detection), Safety Helmet Detection, Off-site Detection
- HTTPS, SSL, Digest Authentication, AES 256
- Encryption, RTSP Validation
- Digital Alarm 1 Ch In/1 Ch Out



AI Video Analytics

Sparsh AI based camera offers real time and high accuracy video analytics function for multiple events such as Motion detection, People Counting, Intrusion, Line Crossing, Missing Object, Wrong Direction Detection, Safety Helmet Detection.



Motion Detection

Motion detection function allows users to monitor specific areas clearly and timely. When motion is detected in the area of interest, the camera will send an alert to an authorized person.

Cyber Security

The camera is more secure and reliable with features such as HTTPS digest authentication, RTSP validation, AES encryption, Watermark, User Authentication, and encrypted firmware.



Technical Specifications:

Specifications	SC-ID42BP- I(Z)(S)
Camera	
Image sensor	1/2.8" Low Illumination Progressive Scan CMOS Sensor
Effective Pixels	2560(H)X1440(V)
Aspect Ratio	16:9
Min. Illumination	Color: 0.001Lux @ (F1.2, AGC ON), 0.014 Lux @ (F1.4, AGC ON), 0 Lux with IR
S/N Ratio	≥58dB (AGC OFF)
IR Distance	2.7-13.5mm:50-60Mtr 5-50mm: 80-100Mtr
Shutter Speed	Auto, Slow Shutter, (1/5 sec ~ 1/100,000 sec Adjustable)
Slow Shutter	On/ Off
WDR	Up to 120 dB, TWDR (Off/ Low/ Middle/ High)
IR LED Control	Auto, Manual, OFF
3D DNR	Low, MID-Low, MID, MID- HIGH, High
Day/Night	ICR switch, Auto, Color, B&W, External Trigger
Defog	Off, Low, Middle, High
Output	PAL/NTSC adjustable
Lens	
Lens Type	VF 2.7-13.5mm (Optional: Motorized VF 2.7-13.5mm, VF 5-50mm, Motorized VF 5-50mm)
Mount Type	M12
IRIS Control	Manual/Auto
Angle Of View	2.7-13.5mm- Horizontal: 121.36° to 34° Vertical: 52° to 19° Diagonal: 116° to 40° 5-50mm- Horizontal: 62° to 7° Vertical: 48° to 5° Diagonal: 75° to 8°
Focus Control	Manual/Auto
Video	
Compression	H.265/H.264/MJPEG
H.265 Encoding	Main Profile
H.264 Encoding	BaseLine / Main Profile / High Profile
Streaming Capability	Quad Streams
Resolution	4MP/2MP/720P/VGA
Streams	Mainstream: 4MP (2560X1440)/1080P(1920X1080)@25/30fps Sub Stream: 720P(1280x720)@25/30fps Third Stream: VGA(640x480)@15fps Fourth Stream: VGA(640x480)@15fps
Frame Rate	1~ 30fps
Video bit Rate	Constant bit rate, variable bit rate (32kbps-12Mbps)
I - Frame	2 -255
Color Mode	Normal, Bright, Nature



*Product specifications & appearance are subject to change without prior notice or obligation.

Exposure Mode	Off, High Light correction, Backlight Correction, Range (1-10)
BLC Mode	1-10 configurable Levels
White Balance	Auto, Manual, Warm light, Natural light, Incandescent lamp, Fluorescent lamp, Locked WB
Gain Control	Low, MID-Low, MID, MID- HIGH, High
Sharpness	0-255
Digital Zoom	25X
Anti - Flicker	Off/ON
AE Algorithms	Shutter Priority, Gain Priority
Mirror	Off, Horizontal Mirror, Vertical Mirror, 180-degree flip
Gamma Mode	Curve 1.6, Curve 1.8, Curve 2.0, Curve 2.2
Privacy Masking	Support 4 area privacy mask
ROI	Support 4 Zone
Display Overlay (OSD)	Title, time and date overlay, multi-line OSD, OSD Color Selection
Image Setting	Brightness, Contrast, Sharpness, Saturation, Chroma
Smart Event	
Motion Detection	Set Detection Area, Period, Can Set Multi-Level Sensitivity
Temper Detection	Support
IVA	People Counting, Vehicle Counting, Human Detection, Electronic Fence (Entry, Exits & Loitering Detection), Line Crossing, Wrong Direction Detection (Retrograde Detection), Safety Helmet Detection, Off-site Detection
Event Actions	Enable Alarm Out, Send Email, Start Recording, Play Customized Audio Warning
PTZ(Manual)	
Pan	0° ~360°
Tilt	0° ~90°
Rotation	0° ~360°
Audio	
Compression	G.711U
Audio Bit Rate	8 – 64 Kbps
Network	
Network Port	RJ45 10M, 100M Network Self Adjustable
Protocol	TCP/IP, IPv4, IPv6, SSL, TLS, UDP, HTTP/HTTPS, HTTP-Base64, HTTP-Digest, DHCP, DNS, DDNS, RTP, RTSP, PPPoE, NTP, UPnP, SMTP, FTP, IGMP, Multicast
System Compatibility	ONVIF Profile S & G
Max. User Access	20 Users
Discovery Interface	UPnP, ONVIF, Sparsh Utility to Detect camera automatically and configure network settings
Web Server	Built In web server with interactive Graphical User Interface
General Function	User Authentication, Watermark, IP address filtering
Security Mode	Authorized username and password, HTTPS with password, AES Encryption for password, RTSP Validation
ANR	Support
Streaming	Unicast & Multicast



Interface	
Audio	Built-In-Mic or 1 IN/1 Out (Optional)
Alarm	1Ch Alarm IN, 1Ch Alarm Out (Optional)
SD Card	Yes, Up to 256GB (Optional)
General	
Operating Conditions	-40 °C ~ 70 °C Humidity 95% or Less (Non-Condensing)
Storage Conditions	-40 °C ~ 70 °C Humidity 95% or Less (Non-Condensing)
Ingress Protection	IP67 Compliant
Vandalism Protection	IK10 Compliant
Surge Protection	TVS 4000V Lightning Protection, Surge Protection & Voltage Transient Protection
Power supply	DC 12V ± 10% / PoE (802.3af)
Power Consumption	<12W
Dimension & Weight	270mm(L) x140mm(W) x 97.7mm(H), 1.3kg
Product Certification	Safety: CE, FCC, EN:60950-1, IS 13252 (Part 1):2010, BIS Registered

Ordering Information:

Sr. No.	Ordering Model	Audio	Alarm	SD Card
1.	SC-ID42BP- I(Z)(S) with VF 2.7-13.5mm lens	NA	NA	NA
2.	SC-ID42BP- I(Z)(S) with VF 2.7-13.5mm lens	Yes	NA	NA
3.	SC-ID42BP- I(Z)(S) with VF 2.7-13.5mm lens	Yes	NA	Yes
4.	SC-ID42BP- I(Z)(S) with VF 2.7-13.5mm lens	Yes	Yes	Yes
5.	SC-ID42BP- I(Z)(S) with Motorized VF 2.7-13.5mm lens	NA	NA	NA
6.	SC-ID42BP- I(Z)(S) with Motorized VF 2.7-13.5mm lens	Yes	NA	NA
7.	SC-ID42BP- I(Z)(S) with Motorized VF 2.7-13.5mm lens	Yes	NA	Yes
8.	SC-ID42BP- I(Z)(S) with Motorized VF 2.7-13.5mm lens	Yes	Yes	Yes
9.	SC-ID42BP- I(Z)(S) with VF 5-50mm lens	NA	NA	NA
10.	SC-ID42BP- I(Z)(S) with VF 5-50mm lens	Yes	NA	NA
11.	SC-ID42BP- I(Z)(S) with VF 5-50mm lens	Yes	NA	Yes
12.	SC-ID42BP- I(Z)(S) with VF 5-50mm lens	Yes	Yes	Yes
13.	SC-ID42BP- I(Z)(S) with Motorized VF 5-50mm lens	NA	NA	NA
14.	SC-ID42BP- I(Z)(S) with Motorized VF 5-50mm lens	Yes	NA	NA
15.	SC-ID42BP- I(Z)(S) with Motorized VF 5-50mm lens	Yes	NA	Yes
16.	SC-ID42BP- I(Z)(S) with Motorized VF 5-50mm lens	Yes	Yes	Yes



*Product specifications & appearance are subject to change without prior notice or obligation.