


- Support IPC resolution up to Ultra HD 4K
- Available in 8/16/32/36 channels
- Video Compression H.265, H.264
- Support up to 5 SATA
- 3G/4G/Wi-Fi Supported
- Intelligent Analytics Supported: All IPC Analytics- Human Detection, Intrusion Detection, Audio Detection, Object Left, Object Lost, Line crossing, Scene Change
- Dual Ethernet Ports
- NDAA Compliant



AI Video Analytics

Sparsh Gold Series can intelligently filter objects to focus on human and vehicle detection in multiple events such as Human Detection, Intrusion Detection, Audio Detection, Object Left, Object Lost, Line crossing, Scene Change.



NDAA Compliant

Our Gold Series Camera is NDAA compliant that conform to the guidelines set by National Defense Authorization Act & do not use components made by the listed prohibited Manufacturers.

4K Resolution

NVR Supports Ultra HD 4K resolution offering detailed quality images at a higher resolution. Provides unmatched clarity and precision, bright colors, with little to no image distortion.



FHD

4K-like Picture

Technical Specifications:

Specifications	SR-NG08F504-H	SR-NG16F805-H	SR-NG32F805-H	SR-NG36F805-H
Video				
Network Video Input	8CH	16CH	32CH	36CH
Operating System	Embedded Linux			
Network Access Bandwidth	80Mbps	960Mbps		
Video Compression	H.265 /H.264			
Video Output	1 CH VGA output (1920×1080, 1280×1024@50/60Hz) 1 CH HDMI output (3840×2160, 1920×1080, 1280×1024, 1440×990 @50/60Hz)			
Video Preview Mode	8ch 4K preview	16ch 4K preview	32ch 4K preview	36ch 5MP preview
Video Bit Rate	16Kbps-16Mbps			
Video Resolution	8MP/5MP/3MP/1080P/720P/D1/VGA/CIF/QCIF			
Preview Capability	8x8MP@25/30fps (Mainstream), 8*D1@25/30fps (Sub Stream)	16x8MP@25/30fps (Mainstream), 16*D1@25/30fps (Sub Stream)	32x8MP@25/30fps (Mainstream), 32*D1@25/30fps (Sub Stream)	32x8MP,36x5MP@25/30f ps (Mainstream), 36*D1@25/30fps (Sub Stream)
Audio	1 Output			
Image Display	1/4/8	1/4/8/16	1/4/8/16/32	1/4/8/16/32/36
Snapshot Mode	Support timing snapshot, manual snapshot, JPEG format			
Motion Detection	Support 396(22*18) surveyed area can be set in every screen and multi-level sensitivity adjustable			
Privacy Mask	Support 4 zones			
Audio				
Audio compression	G.711u			
Audio output	1 RCA			
Video Recording and Playback				
Video Frame Rate	1-30fps			
Record Mode	Manual/Schedule/Motion Detection/timing/intelligent analysis alarm			
Max. Playback Ability	1CH(Main), 8CH(D1)	2CH(Main), 16CH(D1)	2CH(Main), 16CH(D1)	2CH(Main), 16CH(D1)
Playback Mode	Instant playback, Local video, local image, External file playback			
Record Search	Time, calendar, channel search, event search, (regular video, motion detection video, alarm video)			
Video Playback	Start, stop, normal play, back play, forward 30 seconds, backward 30 seconds, fast play (1-256X), slow play(1-1/32X), frame play, display the hidden progress bar, backup, snapshot, full screen, roller amplification time bar precise playback			
Storage and Backup				
Storage Interface	4 SATA	5 SATA		
HDD Capacity	Single max.10TB			
Disk Grouping	According video channels to set HDD quantity			
Disk Quota	According video channels to set HDD storage capacity			
Backup Location	Local, network			
Backup Method	USB Device, network backup			
Network				
Network Protocol	TCP/IP, IPv4, HTTP, PPPoE, DHCP, DNS,3G/4G, Wi-Fi, Google drive/Dropbox Storage(1CH), DDNS, RTP, RTSP, RTCP, NTP, UPnP, SMTP, FTP, P2P, IP Filter			
Interface Protocol	ONVIF, RTSP			



*Product specifications & appearance are subject to
change without prior notice or obligation.

Protocol port	ONVIF/RTSP/HTTP	
Mobile Surveillance	Support iOS, Android	
Internet Explorer	Support IE, Chrome, MS Edge Firefox, Safari	
Event Actions	Send email, audible warning (buzzer), alarm on monitor, upload to center control room, record, snapshot, preview, PTZ linkage	
User Management	User add, delete, modify, permission management, Support dual password authentication, zero passage, Auxiliary users (secondary password protection)	
Security Mode	Authorized username and password, HTTPS with password, RTSP Validation	
Manage IPC	Modify IPC parameters	
Ext Interface		
Network Interface	1 X RJ45 10M/100M adaptive Ethernet port	2 X RJ45 10M/100/1000M adaptive Ethernet port
USB Interface	3 USB2.0	
General		
Power Supply	AC100~240 V	
Power Consumption	≤50W (Without HDD)	
Operation Temperature/ Humidity	-10℃ ~ 60℃/10%-90 %	
Dimension(mm)	260(L)x250(W)x42(H)mm	
Weight/PCS(g)	1.8Kg	
Certification	CE, FCC, EN-60950-1, IEC-60950-1, BIS Certified	



*Product specifications & appearance are subject to change without prior notice or obligation.