


## 64CH NVR

- Support IPC resolution up to Ultra HD 4K
- Supports 64 channels Input
- Video Compression H.265SE, H.265, H.264
- Support up to 8 SATA
- Intelligent Analytics Supported: All IPC Analytics- Human Detection, Intrusion Detection, Audio Detection, Line crossing
- NDAA Compliant



### AI Video Analytics

Sparsh Gold Series can intelligently filter objects to focus on human and vehicle detection in multiple events such as Human Detection, Intrusion Detection, Audio Detection, Line crossing.



### NDAA Compliant

Gold Series NVRs are NDAA compliant that conform to the guidelines set by National Defense Authorization Act & do not use components made by the listed prohibited Manufacturers.

### 4K Resolution

NVR Supports Ultra HD 4K resolution offering detailed quality images at a higher resolution. Provides unmatched clarity and precision, bright colors, with little to no image distortion.



FHD

4K-like Picture

## Technical Specifications:

| Specifications                      | SR-NG64F808-HA   |
|-------------------------------------|--|
| <b>Video</b>                        |  |
| Network Video Input                 | 64 CH  |
| Operating System                    | Embedded Linux   |
| Network Access Bandwidth            | 480Mbps  |
| Video Compression                   | H.265SE/H.265 /H.264   |
| Video Output                        | 1 CH VGA output (1920×1080, 1280×1024@50/60Hz)<br>2 CH HDMI output (3840x2160, 1920×1080, 1280×1024, 1440x990 @50/60Hz)  |
| Video Preview Mode                  | 64ch 8MP preview   |
| Video Bit Rate                      | 16Kbps-16Mbps  |
| Video Resolution                    | 8MP/5MP/3MP/1080P/720P/D1/VGA/CIF/QCIF   |
| Preview Capability                  | 64*8MP@25/30fps (Mainstream),<br>64*D1@25/30fps (Sub Stream)   |
| Audio                               | 1 Input/ 1 Output  |
| Image Display                       | 1/4/8/16/32/36/64  |
| Snapshot Mode                       | Support timing snapshot, manual snapshot, JPEG format  |
| Motion Detection                    | Support 396(22*18) surveyed area can be set in every screen and multi-level sensitivity adjustable   |
| Privacy Mask                        | Support 4 zones  |
| <b>Audio</b>                        |  |
| Audio compression                   | G.711u/a   |
| Audio output                        | 1CH 3.5mm Jack   |
| <b>Video Recording and Playback</b> |  |
| Video Frame Rate                    | 1-30fps  |
| Record Mode                         | Manual/Schedule/Motion Detection/timing/intelligent analysis alarm/Time Warping (Save upto 80% storage space)  |
| Max. Playback Ability               | 2CH(Main), 16CH(D1)  |
| Playback Mode                       | Instant playback, Local video, local image, External file playback, Camera SD Card Remote Playback   |
| Record Search                       | Time, calendar, channel search, event search, (regular video, motion detection video, alarm video)   |
| Video Playback                      | Start, stop, normal play, back play, forward 30 seconds, backward 30 seconds, fast play (1-256X), slow play(1-1/32X), frame play, display the hidden progress bar, backup, snapshot, full screen, roller amplification time bar precise playback |
| <b>Storage and Backup</b>           |  |
| Storage Interface                   | 8 SATA   |
| HDD Capacity                        | Max. 10TB per SATA   |
| Backup Location                     | Local, network   |
| Backup Method                       | USB Device, network backup   |
| <b>Network</b>                      |  |
| Network Protocol                    | TCP/IP, IPv4, HTTP, PPPoE, DHCP, DNS,3G/4G, Wi-Fi, Google drive/Dropbox Storage(1CH), DDNS, RTP, RTSP, RTCP, NTP, UPnP, SMTP, FTP, P2P, IP Filter  |

|                                 |   |
|---------------------------------|---|
| Interface Protocol              | ONVIF, RTSP   |
| Protocol port                   | ONVIF/RTSP/HTTP/HTTPS   |
| Mobile Surveillance             | Support iOS, Android  |
| Internet Explorer               | Support IE, Chrome, MS Edge Firefox, Safari   |
| Event Actions                   | Send email, audible warning (buzzer), alarm on monitor, upload to center control room, record, snapshot, preview, PTZ linkage |
| User Management                 | User add, delete, modify, permission management   |
| Security Mode                   | Authorized username and password, HTTPS with password, RTSP Validation  |
| Manage IPC                      | Modify IPC parameters   |
| <b>Ext Interface</b>            |   |
| Network Interface               | 2 X RJ45 10M/100/1000M adaptive Ethernet port   |
| USB Interface                   | 2 USB2.0, 1USB3.0   |
| Alarm                           | 16 IN/ 4 Out  |
| RS485 Port                      | Support   |
| <b>General</b>                  |   |
| Power Supply                    | AC100~240 V   |
| Power Consumption               | ≤50W (Without HDD)  |
| Operation Temperature/ Humidity | -10°C ~ 60°C/10%-90 %   |
| Dimension(mm)                   | 260(L)x250(W)x42(H)mm   |
| Weight(g)                       | 1.5Kg   |
| Certification                   | Safety: CE, FCC, IS/EN:60950-1, IS:13252 (Part 1): 2010, BIS Registered   |



\*Product specifications & appearance are subject to change without prior notice or obligation.

